

Switch Specifications:


SST Option:

Magnetic Contact, Surface Mount, Electrical Configuration SPDT, Loop Configuration Closed and Open, Lead Size #22 AWG, Material Metal, Max. Current (Amps) 0.2, Max. Voltage 30VDC/VAC, Max. Gap Distance (In.) 1-1/4, Length (In.) 5/8, Height (In.) 3/8, Width (In.) 2, Depth (In.) 5/8, Lead Length (In.) 18, Operating Temp. Range (°F) -15 to 160, Response Time (Sec.) 0.5ms Max.

Plated Steel Option:

Magnetic Contact, Surface Mount, Electrical Configuration SPDT, Loop Configuration, Closed and Open. Operating Temp Range -15-- 160F

NOTES:
-ALL DIMENSIONS IN [] ARE INCHES

DATE DRAWN: 06/19/13 PH	 AJ Manufacturing, Inc Bloomer, WI
UNLESS OTHERWISE SPECIFIED:	TITLE: PRESSURE RELIEF DOOR WITH SWITCH ASSEMBLY
DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: FOLDED ±1/2° WHOLE NUMBER ±1 mm ONE PLACE DECIMAL ±.5 mm	Rev. -
DO NOT SCALE	DWG. # 00862 PART # -