

Inswing - Allegis Latch Installation

Photo # 1

Photo shows latching mechanism.



May 19, 2011

S J Field

Inswing - Allegis Latch Installation

Photo # 2

Place the gasket onto the inner surface of the latch mechanism. Align the small hole in the gasket with the peg on the mechanism.



May 19, 2011

S J Field

Inswing - Allegis Latch Installation

Photo # 3

Insert the latch mechanism shaft into the large hole in the panel.

Note: the side of the door with the large and small hole is considered the "outside".


May 19, 2011

SJ Field

Inswing - Allegis Latch Installation

Photo # 4

Align the mechanism so the small hole in the panel and the "peg" are aligned and push into place.



If necessary, rotate the shaft of the latch mechanism so the inner two cams are on opposite sides of the hex nut.

May 19, 2011

SJ Field

Inswing - Allegis Latch Installation

Photo # 5

Move to the inside of the door and place the inside escutcheon onto the shaft. Remember to orient it so the smaller diameter collar will slide into the bored hole.

May 19, 2011

SJ Field

Inswing - Allegis Latch Installation

Photo # 6

Push the escutcheon all the way to the door surface.

May 19, 2011

SJ Field

Inswing - Allegis Latch Installation

Photo # 7

Using the locking nut*, tighten until the escutcheon just begins to compress the door. Over tightening will impair proper functioning of the latch. Under tightening will cause the latch to wobble.



Caution:
The escutcheon has a one way "tinnerman clip". Once installed, it can not be removed

May 19, 2011

S J Field


Inswing - Allegis Latch Installation

Photo # 8

Inswing door latch for the 1", 2" and 4" thick doors. Note the hole in the side.



Inswing roller cam.




May 19, 2011

S J Field

Inswing - Allegis Latch Installation

Photo # 9



Inswing door latch for the 1.7" thick doors.
Note the smaller hole in the side.


Inswing roller cam for the
1.7 door. Note the offset
on the shaft.

May 19, 2011

SJ Field

Inswing - Allegis Latch Installation

Photo # 10



Determine the handing for the door.
In this case, with the door handle in
the "down" position, the handing
will be "right hand". For "left
hand", insert the roller cam for the
right side.

Position the roller cam with the hole
up, and insert it into the latch
handle.

May 9, 2011

SJ Field

Inswing - Allegis Latch Installation

Photo # 11




On the roller cam for the 1.7" door, position the roller cam with offset down, and insert it into the latch handle.

May 19, 2011

S J Field

Inswing - Allegis Latch Installation

Photo # 12



Align the hole in the cam shaft with the hole in the handle, and insert it in the latch handle.


Note: The steps from photo 12 through photo 20 are the same for both styles of cams.

May 19, 2011

S J Field

Inswing - Allegis Latch Installation

Photo # 13



Insert the machine screw
into the latch handle / roller
cam shaft.

May 19, 2011

S J Field

Inswing - Allegis Latch Installation

Photo # 14



Line up the handle with
the latch mechanism on
the door.

May 19, 2011

S J Field


Inswing - Allegis Latch Installation

Photo # 15




Inswing - Allegis Latch Installation

Photo # 16



Inswing - Allegis Latch Installation

Photo # 17



Take a red inside handle and attach it to the latch mechanism bolt on the inside of the door. Attach so the handle is down and away from the latch frame.

May 19, 2011

SJ Field

Inswing - Allegis Latch Installation

Photo # 18



Screw on a locking nut and tighten.

May 19, 2011

SJ Field

Inswing - Allegis Latch Installation

Photo # 19



When you are satisfied that the handle is correctly orientated in the latching mechanism, install the plastic cover plug.

Note: The inswing latch cannot be adjusted to provide greater compression on the gasket.

May 19, 2011

S J Field

Inswing - Allegis Latch Installation

Photo # 20



Photo shows completed install of the inswing Allegis latch for a "right hand" (inswing) door.

May 19, 2011

S J Field