

**SERIES 3700**  
**PREHUNG 4-WAY UNIVERSAL SWING**  
**WALK DOOR**



**A.J. Manufacturing, Inc.**  
1217 Oak Street  
Bloomer, WI 54724  
P: 800-328-9448  
715-568-2204  
F: 715-568-3099  
www.ajdoor.com

**Building Ideas**

**DOOR TYPE**

- Prehung 4-way universal swing, insulated leaf with aluminum jamb, header and sill.

**DOOR CONSTRUCTION**

- 1-3/4" thick door pressure injected with 2.2 pounds of polyurethane foam per cubic foot.
- 24 gauge hot dipped galvanized smooth steel panels, polyester painted and baked for a durable and long lasting finish.
- Flush design - rolled edges for style, strength, and corrosion resistance.
- Polyurethane foam core for an R12 insulation value.

**MASTER FRAME CONSTRUCTION**

- Frame jamb, header, and sill are fabricated of commercial quality aluminum extrusions 3-1/2" wide with 0.062" minimum wall thickness.
- Frame jamb, header and sill are polyester painted and baked for a durable and long lasting appearance.
- Master frame is shipped completely assembled with hinges and door attached.
- A unique design allows the weatherstripped header parting stop to be snapped in place after the door has been installed to insure a weather tight installation.
- Sill is a low profile design, which complies with the ADA handicap accessible guidelines. It is 3-1/2" deep and 1/2" high.

**HARDWARE**

- Door is mounted to the frame by three, 12 gauge steel, 4-1/2" x 4" fixed pin hinges.
- Hinges are treated with rust inhibitor, painted and lacquer dipped for exterior installation.
- Door is prepped for lockset by boring a 2-1/8" diameter hole with a 2-3/4" backset and a 1" edge bore.
- Door panel is strengthened with an extruded aluminum reinforcing block at the location for entry lock.

## WEATHERSTRIPPING

- Master frame is weatherstripped with woven polypropylene pile.
- Top and bottom sill sweeps are fabricated of a dual durometer vinyl consisting of three flexible wands on a rigid base.

## DOOR LITES

Series 3700 door may be ordered with five different types of door lites

1. 22" x 22" Single Glazed Vue Lite, consisting of 1 piece of 1/8" tempered glass.
2. 22" x 22" Insulated Vue Lite, consisting of 2 pieces of 1/8" tempered glass with 1/2" dead air space.
3. 22" x 36" Insulated 1-Lite, consisting of 2 pieces of 1/8" tempered glass with 1/2" dead air space.
4. 22" x 36" Insulated 9-Lite, consisting of 2 pieces of 1/8" tempered glass with a rigid aluminum grid system installed within the 1/2" dead air space.
5. 22" x 36" Insulated Vent Lite, consists of a 3/4" tempered glass unit with one fixed sash, one operating sash and screen.

All door lites are installed in pre-painted color matched extruded aluminum frames, which are foamed in place. A bonding type black bedding glazing tape provides a watertight seal and secures the glass in the opening. Glazing is completed with a snap-in dual durometer glazing bead.