



PREHUNG 4 WAY-UNIVERSAL WALK DOORS 3100—3700

Available In: Standard • Vue Lite • 9-Lite • Crossbuck with 9-Lite



Count on A.J. Manufacturing

Time tested performance built into every door. The fully weather-stripped aluminum frame, 4"x 4-1/2" zinc coated hinges, foamed panel and the industries best warranty deliver durability and performance year after year.

Features & Benefits: (all doors)

- Prehung 4-way universal
- 1-3/4" thick door panel
- Pressure injected with 2.2 pounds of polyurethane foam per cubic foot
- R-14 insulation value
- White panels and jambs
- Rolled edge door panel

Warranty

A.J.'s Prehung 4 Way-Universal Walk Doors are designed and manufactured with quality materials and workmanship. The 5 year warranty applies to defective materials or workmanship. The warranty commences from the date of manufacture. At A.J.'s discretion, replacement or repair of product will be provided. Expenses associated with transportation and installation costs are at the owner's expense.

PREHUNG 4 WAY-UNIVERSAL WALK DOORS 3100—3700

Prehung four-way universal swing entry door fin/J-channel jamb

3100

- 28 gauge embossed steel skin
- Woven polypropylene pile weather-stripping

3150

- 3100 panel in an aluminum nailing fin/J-channel jamb

3700

- 24 gauge smooth steel skin
- Woven polypropylene pile weather-stripping
- Panel available with crossbuck stamped design

3750

- 3700 panel in aluminum nailing

Additional Features:

- Prepainted with two coats of polyester paint for a durable and long lasting finish
- Door is mounted to the frame by three 12-gauge steel, 4-1/2" x 4" fixed pin hinges
- Hinges zinc plated for rust resistance
- 2'4" to 4'0" widths and double doors standard
- Prehung door individually cartoned
- Designed for steel, masonry and wood construction
- All lites are aluminum framed and foamed in place

DOOR CONSTRUCTION

28 gauge hot dipped galvanized embossed steel panels
24 gauge hot dipped galvanized smooth steel panels
Panel strengthened with c-channel at entry lock

WEATHER-STRIPPING

Master Frame weather-stripped with woven polypropylene pile

PANEL OPTIONS

Standard Panel, No Lite

22"x 22" Vue Lite fabricated of 1/8" tempered glass

22"x 36" 1-Lite sealed insulated glass consisting of two of pieces 1/8" tempered glass

22"x 36" 9-Lite sealed insulated glass consisting of two pieces 1/8" tempered glass with a rigid aluminum grid system

22" x 22" Insulated Vue Lite consisting of two pieces 1/8" tempered glass

COLORS

White, painted jamb and panel

	3100	3700
Standard Panel, No Lite	■	
22"x 22" Vue Lite	■	■
22"x 36" 1-Lite	■	■
22"x 36" 9-Lite	■	■
22" x 22" Insulated Vue Lite	■	■
Crossbuck 9-Lite	■	■

Standard Jamb
(3100, 3700)

Nailing Fin
J-channel Jamb
(3150 and 3750)

Aluminum Frame
Aluminum stile of door is reinforced for added strength

Polyurethane foam core guaranteed not to swell, delaminate or warp

Top and bottom sill sweeps are fabricated of a dual durometer vinyl consisting of three flexible wands and rigid base

Aluminum 1/2" Code Approved Low Profile Threshold



AJ MANUFACTURING, INC.
BUILDING IDEAS

800-328-9448 @ www.ajdoor.com



Standard (flush)



Vue Lite (22"x 22")



9-Lite (22"x 26")



Crossbuck 9-Lite