

Attic Access Door

AN ENGINEERED SOLUTION TO ATTIC ACCESS

Durable / Attractive Energy Saving / Easy Installation

Save Time, Energy and Money

- Self-flashing
- Factory installed gasket
- Ready to install
- Pre-hung

Add Value

- Quality construction
- Durable finish
- Energy efficient

Door Type and Construction

This high performance double wall ceiling access door is for buildings with an interior ceiling liner. The white 1" thick steel door panel has a white self-flashing pre-hung aluminum frame that can be mounted in trusses, 24" or 48" on center.

- Hot dipped galvanized G60 steel skin
- 1" thick door with an expanded polystyrene core
- White polyester painted steel sheet creates a seamless rigid panel with an insulating value of R6.5

Master Frame Construction

- Frame is fabricated of commercial quality 0.062" painted aluminum extrusions
- Master frame is shipped completely assembled with stainless steel hinges and door attached
- Self-flashing frame extrusions are miter cornered and assembled with screws for strength

Hardware

- Door is mounted to the frame by (2) fixed pin stainless steel hinges
- Door panel is reinforced at the pull handle location to provide maximum strength and performance
- An egress pull cord is installed in the attic side of the panel

Sizes Available

- 24" X 36" Nominal Size
(rough opening 22 9/16" X 34 9/16")
20" x 32" Egress
- 24" X 48" Nominal Size
(rough opening 22 9/16" X 46 9/16")
20" x 44" Egress



Durable finish and energy efficient.



Perfect for post frame buildings with an interior ceiling.



Large opening for easy attic access.



A. J. Manufacturing, Inc.
1217 Oak Street
Bloomer, WI 54724
1-800-328-9448
www.ajdoor.com

Building Ideas