



Insulation Dam Kit

Must Have - Time Saver

- Patent Pending

- Saves Time (installation)
- Saves Cost (materials & energy)
- Easy Install (just minutes)
- Ships Flat
- 24" x 36 & 24" x 48"
- G90 Galvanized 24 ga Steel
- Hemmed Top Edge (for safety)
- Installs from below the ceiling through the door opening
- "Key" Holds Door Open
- Universal Panels for all A.J. CAD panel thicknesses
- No Special Tools Required
- Designed for up to R60 - 20" tall
- Can be used with:
 - A.J. 1" R7 CAD
 - Patent Pending 4" (R32) CAD
 - Patent Pending 6" (R48) CAD

R60
is 20" of blown cellulose or fiberglass batt

R50
is 15" of blown cellulose or fiberglass batt

R30
is 10" of blown cellulose or fiberglass batt

Kit components:

- Two (2) universal - narrow end panels (shipped flat with hem/fold on the top)
- Two (2) universal - long side panels (shipped flat with a hem/fold on the top)
- One (1) door retaining KEY – (shipped flat)

- All bending done by hand along the perforation running from the top (hem/fold) of each panel to the bottom of the panel.
- Bending of the corner locking tabs will be done by hand.
- The KEY for holding the door open is hand bent into a "U" shape.



Viewed from Attic

